

DH1



Hot Water Hose

Application:

Mainly used as a cooling or hot water hose in the iron and steel industry.

Feature:

The vulcanised glass fabric cover protects against high external temperatures, radiation heat and sparks.

Notice:

- On request:
- with 3 glass fabric covers
 - white tube
 - Nomex® cover.

ATTENTION: It is vital to be aware of the different working pressures.

Temperature range:

+95°C for hot water, radiation temperature approx. 300°C (with 1 gfc - DH1),
approx. 500°C (with 3 gfc - DH3).

Safety factor:

3,15 : 1

Tube:

SBR, black, smooth.

Reinforcement:


Textile wrapped.

Cover:

Glass fabric cover.

Marking:

none



Article number	Internal-Ø in		Wall width	External-Ø		Work. pressure (max.) bar	Number of inserts	Bending radius	Weight approx. kg/m	Coil length (max.) m
	mm	inch	in mm	in mm	(min.) in mm					
48337 1355	13,0	1/2	5,5	24,0	12	2	50	0,50	40	
48337 1955	19,0	3/4	5,5	30,0	12	2	95	0,60	40	
48337 2560	25,0	1	6,0	37,0	12	2	125	0,75	40	
48337 3260	32,0	1 1/4	6,0	44,0	12	2	160	1,00	40	
48337 3560	35,0	1 3/8	6,0	47,0	12	2	175	1,15	40	
48337 3870	38,0	1 1/2	7,0	52,0	12	2	190	1,35	40	
48337 3880	38,0	1 1/2	8,0	54,0	12	2	200	1,55	40	
48337 4070	40,0		7,0	54,0	10	2	200	1,45	40	
48337 5070	50,0		7,0	64,0	8	2	250	1,75	40	

DH1.....with 1 glass fabric cover (acc. to table), DH3.....with 3 glass fabric covers (on request)

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website (www.semperflex.com) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively subject to our general terms and conditions (available at www.semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found at our website (www.semperflex.com) and must be followed without exception.

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the latest state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620: 2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to the continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance or handling (e.g. squashing, rupturing, stretching or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to EN ISO 1307:2008.